



# FLOETROL®

## WATERBORNE PAINT CONDITIONER

### USAGE


- Add to any waterborne paint.

### PROPERTIES

- Improves flow, minimises and often eliminates brush marks.
- Gives a spray like finish when using a roller, especially on deep colours like terracotta etc.
- Helps hiding power on low hide colours such as yellow, red etc.
- Saves a lot of time when using a roller.
- Increases the wet edge time, ideal for special effects like marbling, rag rolling, sponging etc.
- Unlike damaging thinners FLOETROL® maintains the inherent quality of the paint without affecting its appearance or drying time.
- Facilitates spray and reduces equipment pressure.



- 1 Paint without FLOETROL®.
- 2 Paint + 10% FLOETROL®, covers 20% more



### APPLICATION

- Always test for compatibility.
- Prepare the surface according to instructions on the paint can.
- Apply the paint.
- If the paint drags, sets too fast or does not level properly, add FLOETROL® until the paint works smoothly, easily and provides a sufficient wet edge.
- As a guide –  
Brush and roller application:  
Add between 7-15% per litre of paint.  
Spray: 5-10% per litre of paint.  
Airless spray: 10% per litre of paint.  
Decorative effects: 20-25% per litre of paint.
- FLOETROL® is ideal for spraying. It reduces spray pressure, overspray and clogging. Ensures better coverage and saves time.

<b>APPLICATION TOOLS</b> 	<b>TEMPERATURE FOR APPLICATION</b> +35°C +5°C	<b>CLEAN UP SOAP + WATER</b> 
------------------------------	-----------------------------------------------------	----------------------------------



#### Owatrol International SL

C/Aragón 179, 5° - 08011 Barcelona - Spain  
Tel: +34 934 51 66 04 - Fax: +34 934 52 14 54  
info@owatrol.com - www.owatrol.com