



OWATROL® E-B

BONDING PRIMER

USAGE

- Additive for paint and varnish.
- Can be used on all surfaces, especially suitable for unstable, chalky and powdery surfaces as well as for difficult surfaces such as glass, plastic, wood, varnished surfaces etc.
- Can be used as a primer or mixed with paint.

PROPERTIES

- E-B acts as a stabiliser, penetrating deep into the surface to firmly bond the first coat of paint to the substrate, thus eliminating need for primer.
- Ensures an even coverage and maximum adhesion between the first and second coat of paint.
- E-B's high solids content maintains the inherent characteristics of the paint, improves hiding power and increases coverage by up to 20%.
- No peeling.
- Odour free.

PERCENTAGE OF OWATROL E-B MIXED WITH PAINT, ONLY IN FIRST COAT

Surfaces that have not been painted	Non-porous and stable	30% EB
	Porous and chalky	50% EB
Surfaces that have already been painted	Stable	25% EB
	Stable, previously painted with white wash, silicate or pliolite	30% EB
	Chalky	50% EB
	Varnished	30% EB
Unstable surfaces or in very bad shape		50% EB
Specific surfaces	Wood, plastic, glass	50% EB
	Vinyl coated paper	25% EB



APPLICATION

- Always test for compatibility.
- Make sure the surface is clean and free from grease; remove any flaky paint.
- For the proportions E-B/Paint see table. (For very chalky surfaces E-B can be used alone. Allow to dry for 24-48h.)
- Use E-B in first coat of paint only.
- After application of the E-B/paint mix allow to dry approx 4 hours.
- Apply second coat of paint without E-B.



APPLICATION TOOLS 	TEMPERATURE FOR APPLICATION +35°C +5°C	DRYING TIME 2-4 hours RECOATING TIME 4 hours	CLEAN UP SOAP + WATER
------------------------------	---	---	-------------------------------------



Owatrol International SL

C/Aragón 179, 5º - 08011 Barcelona - Spain
 Tel: +34 934 51 66 04 - Fax: +34 934 52 14 54
 info@owatrol.com - www.owatrol.com